



MAXITROL SENTRY GS - SERIES

Excess Flow Valve solution for AS/NZS5601.1 Clause 5.2.11

	<u>PART No. KBG25HH 6AID1</u>	
	Model Series	GS25-6D Sentry EFV
	Working Pressure	15mbar - 100mbar
	GAS Meter Model	Model U10 10 m³/h
	P-max Flow	p-max 10m³/h = 400Mj/Hr
	Nominal flow	6.0 m³/h - (8.70 m³/h)
	Shut-off	Shut-Off = 350Mj.
	Orientation	Male Inlet X Fem Outlet
	Flow Direction	Vertical Downward
	Thread Standard	DN25 ISO 7(Rp.)

***WARNING* maximum Gas Meter flow rate must be greater than EFV shut-off rate**

	<u>PART No. KBG25HH 6AIZ1</u>	
	Model Series	GS25-6Z Sentry EFV
	Working Pressure	15mbar - 100mbar
	GAS Meter Model	Model U10 10 m³/h
	P-max Flow	p-max 10m³/h = 400Mj/Hr
	Nominal flow	6.0 m³/h - (8.70 m³/h)
	Shut-off	Shut-Off = 350Mj.
	Orientation	Fem Inlet X Male Outlet
	Flow Direction	Vertical-up / Horizontal
	Thread Standard	DN25 ISO 7(Rp.)

***WARNING* maximum Gas Meter flow rate must be greater than EFV shut-off rate**